




Double Remaining Heat Indicator Type 423



Tolerances unless otherwise stated: ± 0.2

Scale: 1:2


Double indicator light for building in.

For use at high temperatures as backlighting behind a diffuse panel, f.e. in glass ceramic appliances as residual heat indicator, fixed by snap-in.

Different voltages, brightnesses, resistances to temperature, conformity marks and also with special specifications available.

For details, please see our web page.

Recommended cutout



Scale: 1:2



electrónica de precisión, s.a.

C./ Galileu, 17 Polígono Industrial Can Estella
E-08635 Sant Esteve Sesrovires
BARCELONA

Tel.: +34 93 774 69 10
Fax.: +34 93 774 65 00
e-mail: epsa@edep.com
http://www.edep.com



Technical specifications series 423

This double or single indicator light for building in is designed for snap-in mounting to rear panel and to be used at high ambient temperatures. The one or two signals can be placed on different positions.

The thermoplastic housing incorporates the fixing elements, the connection means and also the lighting means.

Usually placed behind a diffusing panel (f. e. of ceramic glass), his black housing prevents from not desired light output or contrasts through it. The incorporated white reflectors improve the brightness and optical appearance.

Following specifications are a guide for end users:

Connection means: Tabs (male terminals) 6.3 x 0.8 (vertical or horizontal)

Ambient temperature: To be used at a ambient temperature of maximum 180 °C or 200°C

Rated voltage: 130V (can be used down to 110V), 250V (can be used down to 220V), 400V (can be used down to 370V) for all voltages, please see "Lighting means"

Nature of supply: AC and DC

Lighting means Neon glowlamps

Colour of lighting mean: orange

Applicable standard: VDE 0710 and, as far es applicable, IEC 598 (EN 60 598)

Conformity marks:  available

Voluntary conformity marks: 

Notes and other technical specifications:

Life expectancy: The ultra high bright glowlamps have an averagelife of 10.000 hours at ambient temperature of 25°C. These values are given for AC supply and standard types. Hease ask for specifications for other types.

Quench resistor: Indicator lights with glowlamps can light a little bit because of the proximity of induction, a lot of cables, or large currents in the mains, even if one pole of the source is disconnected. This phenomenon is solved either with two pole disconnection or incorporating an additional paralel resistor.

Other voltages: Under request also other voltages for different natures of supply can be offered.

Other ambient temperature: If the indicator light has to work at other ambient temperatures, ask for special quote.

Brightness: Our indicator has a very high brightness light output. Other brightnesses available under request. The life expectancies vary from those specified above.

Recycling: The housing is marked with the identification of his thermoplastic material.

Order Instructions

For orders, please indicate: Type reference, number of signals and if only one also his position, nominal voltage, connection means (in detail), ambient temperature of use and also equipment of the light reflectors.

Examples: Indicator light, double, 423, 250V, horizontal tabs 6.3 x 0.8, 180°C, distance d reflectors 20 mm or Indicator light type 423, single (position detailed on sketch), 130V, 200°C, vertical tabs,

Any special requeriment (f. e. specific plastic raw material, other ambient temperature, other lighting means, other voltages, quench resistor and his ohmic value, other connection means, a. s. o.) is considered a special execution and his supply and order identification has to be confirmed specially by us.

These details are necessary for the first order and to be in accordance with the prescriptions of product identification of the standard(s) and (or) of the certification institute(s).

For following orders this can be substituted by a code of ten numbers which we assign toall our products and coincides with our drawing number, which usually has to be made to assure corect product identification.